



## KBU 35-2 QW

Universal magnetic core drill for up to 35 mm

Small and powerful 2-speed universal magnetic core drill with clockwise/anti-clockwise operation and high speed for efficient twist drilling on the construction site.

Product number: 7 270 58 61 00 0

## Details

- + Extremely low-wear tool design with swivel-mounted motor cable protection hose for tough use in industry and manual trades.
- + Extremely resilient construction thanks to sturdy machine design with swivel-mounted motor cable protection hose. Designed for tough use in industry and manual trades.
- + Perfect power-to-weight ratio thanks to compact, weight-optimised design and FEIN 1 100 W high-power motor with tacho electronics for high speed stability for reliable and economical working.
- + With clockwise/anti-clockwise operation, electronic speed setting and a 260 mm stroke range, this is a universal tool for core drilling, twist drilling, tapping, countersinking and reaming.
- + Small with mechanical 2-speed gearbox for twist drilling.
- + Simple operating concept avoids mix-ups and can be clearly seen by the user.
- + Convenient magnetic holding force display helps the user to reliably position the tool.
- + High magnetic holding force thanks to 2-coil magnet, just 70 mm wide.
- + Tilt sensor.
- + Additional magnetic switch in the drill jig.
- + Integrated coolant tank delivers long core drill bit lives.
- + Feed handwheel can be moved from one side to the other.
- + Speed saving "memory function".
- + Personal safety switch.

## Price includes

- + 1 coolant tank
- + 1 swarf hook
- + 1 contact guard
- + 1 lashing strap
- + 1 centering pin
- + 1 case

## Product feature

- + Magnetic holding force display
- + Variable speed control
- + Speed-controlled electronics (tacho)
- + Reversible rotation
- + Memory function
- + Tilt sensor

## Application

Core drilling in metal with a Ø up to 35 mm

Twist drills with drill chuck (DIN 338)

Tapping

++

++

++

++



# FEIN

Countersinking

Reaming

Working overhead

Installation work

Workshop jobs

++

++

++

++

+ suitable

++ well suitable

## Technical data

### TECHNICAL DATA

### VIBRATION AND SOUND EMISSION VALUES

Input

1,100 W

Output

550 W

Load speed in speed 1

130 - 520 rpm

Load speed in speed 2

400 - 1,600 rpm

Carbide core drill bit max.  
Ø

35 mm

HSS core drill max. Ø

35 mm

Core drill, drilling depth  
max.

50 mm

Twist drill max. Ø

16 mm

Tapping

M 14

Countersinking max. Ø

31 mm

Reaming max. Ø

16 mm

Core drill holder

3/4 in Weldon

Sound pressure level LpA  
Uncertainty of measured value  
KpA

83,2 dB  
5 dB

Sound power level LWA  
Uncertainty of measured value  
KWA

94,2 dB  
5 dB

Sound peak value  
LpCpeak  
Uncertainty of measured value  
KpCpeak

96,8 dB  
5 dB

Vibration value 1  $\alpha_{hv}$  3-  
way  
Uncertainty of measured value  
K $\alpha$

$\alpha_{h,D} < 2,5 \text{ m/s}^2$   
1,5 m/s<sup>2</sup>



Changing the core bit

tool-free

Stroke

135 mm

Total stroke range

260 mm

Cable with plug

4 m

## Application examples

