



## AKFH 18-5 AS

### Cordless beveller up to 5 mm

Powerful cordless beveller for perfectly preparing subsequent coatings for flexible jobs in the workshop and on the construction site.

Product number: 7 138 02 62 00 0

## Details

- + For the production of bevels and radii on flat materials, sheet metals and containers, of inner and outer edges, contour shapes and for rounding off holes.
- + High sanding capacity requiring little force and infinitely variable speed setting for different materials.
- + Ergonomic thanks to low weight and compact design.
- + FEIN PowerDrive motor delivers good performance and long service life.
- + Extensive user protection features include soft start, restart protection, jam monitoring and electronic overload protection.
- + Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- + ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- + COOLPACK 2.0 technology delivers a 135% longer battery life and therefore makes longer operating times possible.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.

## Price includes

- + 1 tool incl. 45 milling head (without guide roller, without indexable tips)
- + 1 x copper paste
- + 1 x TX 15 Torx screwdriver
- + 3 x clamping screws SX
- + 1 x 4 mm socket head wrench
- + 1 plastic tool case (L-BOXX 238)

## Product feature

- + Soft start
- + Blockage monitoring
- + Speed preselection
- + Restart protection
- + Electronic overload protection

## Application



Installation work

++

Bevel length of up to 5 mm at 45°

+

Workshop jobs

+

+ suitable

++ well suitable

## Technical data

### TECHNICAL DATA

Battery voltage

18 V

Battery compatibility

Li-ion / ProCORE Li-ion

Battery interface

18 V AMPShare

Speed, no load

2,400 - 7,500 rpm

Max. bevel length at 45°

5 mm

Max. bevel height at 45°

3.5 mm

Bevel angle

45°

Radius

1.2 / 2,5 mm

Milling head  
configuration

3x SX tip

Support plate diameter

98 mm

Weight without storage  
battery

2.52 kg

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA  
Uncertainty of measured value  
KpA

85 dB  
3 dB

Sound power level LWA  
Uncertainty of measured value  
KWA

96 dB  
3 dB

Sound peak value  
LpCpeak  
Uncertainty of measured value  
KpCpeak

100 dB  
3 dB

Vibration value 1  $\alpha_{hv}$  3-  
way  
Vibration value 2  $\alpha_{hv}$  3-way

3,1 m/s<sup>2</sup>  
4,5 m/s<sup>2</sup>

Uncertainty of measured  
value K $\alpha$

1,5 m/s<sup>2</sup>

## Application examples



# FEIN

